



Cummins Inc.

Columbus, Indiana 47201

Engine Data Sheet

Basic Engine Model:
QSX15-G8

Engine Critical Parts List:
CPL: 2816

Curve Number:
FR-10302

Date:
30Oct01

**G-DRIVE
QSX
1**

Displacement : **15 liter (912 in³)**

Bore : **137 mm (5.39 in.)** Stroke : **169 mm (6.65 in.)**

No. of Cylinders : **6**


Aspiration : **Turbocharged and Charge Air Cooled**

•• PRELIMINARY ••

Engine Speed RPM	Standby Power		Prime Power		Continuous Power	
	kWm	BHP	kWm	BHP	kWm	BHP
1500	500	670	451	605	317	425
1800	485	650	436	585	306	410


Engine Performance Data @ 1500 RPM

OUTPUT POWER			FUEL CONSUMPTION			
%	kWm	BHP	kg/ kWm-h	lb/ BHP-h	liter/ hour	U.S. Gal/ hour
STANDBY POWER						
100	500	670	0.204	0.334	120	31.7
PRIME POWER						
100	451	605	0.197	0.325	105	27.7
75	339	454	0.199	0.327	79.0	20.9
50	226	303	0.207	0.341	55.0	14.5
25	113	151	0.217	0.357	27.0	7.5
CONTINUOUS POWER						
100	317	425	0.200	0.329	74.6	19.7



Engine Performance Data @ 1800 RPM

OUTPUT POWER			FUEL CONSUMPTION			
%	kWm	BHP	kg/ kWm-h	lb/ BHP-h	liter/ hour	U.S. Gal/ hour
STANDBY POWER						
100	485	650	0.202	0.332	115	30.4
PRIME POWER						
100	436	585	0.200	0.329	102	26.9
75	327	439	0.201	0.331	77.5	20.5
50	219	293	0.208	0.343	53.4	14.1
25	109	146	0.236	0.389	30.3	8.0
CONTINUOUS POWER						
100	306	410	0.203	0.334	72.7	19.2



CONVERSIONS: (liters = U.S. Gal x 3.785) (Engine kWm = BHP x 0.746) (U.S. Gal = liters x 0.2642) (Engine BHP = Engine kWm x 1.34)

Data shown above represent gross engine performance capabilities obtained and corrected in accordance with ISO-3046 conditions of 100 kPa (29.53 in Hg) barometric pressure [110 m (361 ft) altitude], 25 °C (77 °F) air inlet temperature, and relative humidity of 30% with No. 2 diesel or a fuel corresponding to ASTM D2.



See reverse side for application rating guidelines.

The fuel consumption data is based on No. 2 diesel fuel weight at 0.85 kg/liter (7.1 lbs/U.S. gal).



Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan, optional equipment and driven components.

•• PRELIMINARY ••

QSX15-G8
1500 RPM



QSX15-G8
1800 RPM



Reference Standards:

BS-5514 and DIN-6271 standards are based on ISO-3046.

Operation At Elevated Temperature And Altitude:

The engine may be operated at:

1800 RPM up to 800 m (2460 ft) and 40 °C (104 °F) without power deration.

1500 RPM up to 750 m (2460 ft) and 40 °C (104 °F) without power deration.

Note: Derates shown are based on 10 in H₂O air intake restriction and 2 in Hg exhaust back pressure.

POWER RATING APPLICATION GUIDELINES FOR GENERATOR DRIVE ENGINES

These guidelines have been formulated to ensure proper application of generator drive engines in A.C. generator set installations. Generator drive engines are not designed for and shall not be used in variable speed D.C. generator set applications.

STANDBY POWER RATING is applicable for supplying emergency power for the duration of the utility power outage. No overload capability is available for this rating. Under no condition is an engine allowed to operate in parallel with the public utility at the Standby Power rating.

This rating should be applied where reliable utility power is available. A standby rated engine should be sized for a maximum of an 80% average load factor and 200 hours of operation per year. This includes less than 25 hours per year at the Standby Power rating. Standby ratings should never be applied except in true emergency power outages. Negotiated power outages contracted with a utility company are not considered an emergency.

CONTINUOUS POWER RATING is applicable for supplying utility power at a constant 100% load for an unlimited number of hours per year. No overload capability is available for this rating.

PRIME POWER RATING is applicable for supplying electric power in lieu of commercially purchased power. Prime Power applications must be in the form of one of the following two categories:

UNLIMITED TIME RUNNING PRIME POWER

Prime Power is available for an unlimited number of hours per year in a variable load application. Variable load should not exceed a 70% average of the Prime Power rating during any operating period of 250 hours.

The total operating time at 100% Prime Power shall not exceed 500 hours per year.

A 10% overload capability is available for a period of 1 hour within a 12 hour period of operation. Total operating time at the 10% overload power shall not exceed 25 hours per year.

LIMITED TIME RUNNING PRIME POWER

Prime Power is available for a limited number of hours in a non-variable load application. It is intended for use in situations where power outages are contracted, such as in utility power curtailment. Engines may be operated in parallel to the public utility up to 750 hours per year at power levels never to exceed the Prime Power rating. The customer should be aware, however, that the life of any engine will be reduced by this constant high load operation. Any operation exceeding 750 hours per year at the Prime Power rating should use the Continuous Power rating.

•• PRELIMINARY ••

Cummins Inc.
Engine Data Sheet

ENGINE MODEL : QSX15-G8

CONFIGURATION NUMBER : D103003GX03

DATA SHEET : DS-10302

DATE : 3Oct01

PERFORMANCE CURVE : FR-10302

INSTALLATION DIAGRAM

• Fan to Flywheel : 3170370

CPL NUMBER

• Engine Critical Parts List : 2816

GENERAL ENGINE DATA

Type.....	4 Cycle; In-line; 6-Cylinder Diesel	
Aspiration.....	Turbocharged and Charge Air Cooled	
Bore x Stroke..... — in x in (mm x mm)	5.39 x 6.65 (137 x 169)	
Displacement..... — in ³ (liter)	912 (15)	
Compression Ratio.....	17 : 1	
Dry Weight..... — lb (kg)	3020	(1370)
Wet Weight..... — lb (kg)	3250	(1475)
Moment of Inertia of Rotating Components		
• with FW 1022 Flywheel..... — lb _m • ft ² (kg • m ²)	106.7	(4.5)
• with FW 1025 Flywheel..... — lb _m • ft ² (kg • m ²)	192.0	(8.1)
Center of Gravity from Front Face of Block..... — in (mm)	19	(483)
Center of Gravity above Crankshaft Centerline..... — in (mm)	10	(255)
Maximum Static Loading at Rear Main Bearing..... — lb (kg)	5400	(2450)

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Block..... — lb • ft (N • m) 1500 (2034)

EXHAUST SYSTEMMaximum Back Pressure at Standby Power Rating..... — in Hg (mm Hg) 2 (50.8)
Maximum Bending Moment to the Turbo Flange..... — lb • ft (N • m) 11 (15)**AIR INDUCTION SYSTEM**Maximum Temperature Rise Between Engine Air Inlet and Intake Manifold..... — °F (°C) 43 (24)
Maximum Intake Air Restriction Including Air Filter Plumbing
• with Dirty Filter Element..... — in H₂O (mm H₂O) 25 (635)
• with Clean Filter Element..... — in H₂O (mm H₂O) 15 (381)**COOLING SYSTEM**Maximum Allowable Pressure Drop from Turbo Outlet to Intake Manifold..... — in Hg (mm Hg) 4 (102)
Coolant Capacity — Engine Only..... — US qt (liter) 25 (24)
Maximum Coolant Friction Head External to Engine — 1800 rpm..... — psi (kPa) 10 (69)
— 1500 rpm..... — psi (kPa) 8 (55)
Maximum Static Head of Coolant Above Engine Crank Centerline..... — ft (m) 46 (14)
Standard Thermostat (Modulating) Range..... — °F (°C) 180 - 200 (82 - 93)
Minimum Pressure Cap..... — psi (kPa) 10 (70)
Maximum Top Tank Temperature for Standby / Prime Power..... — °F (°C) 230 / 220 (110 / 104)**LUBRICATION SYSTEM**Oil Pressure @ Idle Speed (Minimum)..... — psi (kPa) 20 (138)
@ Pressure Range — Cold..... — psi (kPa) Up to 130 (Up to 900)
— Warm..... — psi (kPa) 35 - 40 (242 - 276)
Maximum Oil Temperature..... — °F (°C) 250 (121)
Oil Capacity with OP 1493 Oil Pan : High - Low..... — US gal (liter) 22 - 19 (83 - 72)
Total System Capacity (Including Filter)..... — US gal (liter) 24 (91)
Angularity of OP 1493 Oil Pan — Front Down..... 5°
— Front Up..... 5°
— Side to Side..... 5°

FUEL SYSTEM

Type Injection System.....	Cummins HPI-TP
Maximum Restriction at OEM Inlet Connection	5.0 (127)
Maximum Allowable Head on Injector Return Line (Consisting of Friction Head and Static Head).....	6.5 (165)
Maximum Fuel Flow to Injection Pump.....	112 (424)
Maximum Fuel Inlet Temperature.....	160 (71)
Maximum Return Fuel Flow	102 (386)
Maximum Return Fuel Temperature @ 160°F (71°C) Fuel Inlet Temperature	210 (99)
Minimum Fuel Tank Vent Capability	1.2 (.55)

ELECTRICAL SYSTEM

Cranking Motor (Heavy Duty, Positive Engagement)	— volt	24
Maximum Allowable Resistance of Cranking Circuit.....	— ohm	0.002
Minimum Recommended Battery Capacity		
• Cold Soak @ 50 °F (10 °C) and Above	— 0°F CCA	600
• Cold Soak @ 32 °F to 50 °F (0 °C to 10 °C).....	— 0°F CCA	640
• Cold Soak @ 0 °F to 32 °F (-18 °C to 0 °C).....	— 0°F CCA	900

COLD START CAPABILITY

Minimum Ambient Temperature for Cold Start with Coolant Heater to Rated Speed	— °F (°C)	7	(-14)
Minimum Ambient Temperature for Unaided Cold Start to Low Idle Speed	— °F (°C)	25	(-4)
Minimum Ambient Temperature for NFPA 110 Cold Start (90°F minimum coolant temperature)	— °F (°C)	32	(0)

PERFORMANCE DATA

- All data is based on:
- Engine operating with fuel system, water pump, lubricating oil pump, air cleaner and exhaust silencer; not included are battery charging alternator, fan, and optional driven components.
 - Engine operating with fuel corresponding to grade No. 2-D per ASTM D975.
 - ISO 3046, Part 1, Standard Reference Conditions of:

Barometric Pressure	: 100 kPa (29.53 in Hg)	Air Temperature	: 25 °C (77 °F)
Altitude	: 110 m (361 ft)	Relative Humidity	: 30%

Steady State Stability Band at any Constant Load	— %	+/- 0.25%
Estimated Free Field Sound Pressure Level of a Typical Generator Set;		
Excludes Exhaust Noise; at Rated Load and 7.5 m (25 ft); 1800 rpm / 1500 rpm	— dBA	89.0 / 89.5
Exhaust Noise at 1 m Horizontally from Centerline of Exhaust Pipe Outlet Upwards at 45°; 1800 rpm / 1500 rpm	— dBA	125 / 123

Governed Engine Speed.....	— rpm
Engine Idle Speed	— rpm
Gross Engine Power Output.....	— BHP (kW _m)
Brake Mean Effective Pressure	— psi (kPa)
Piston Speed.....	— ft / min (m / s)
Friction Horsepower	— HP (kW _m)
Engine Water Flow at Stated Friction Head External to Engine:	
• 3 psi Friction Head	— US gpm (liter / s)
• Maximum Friction Head.....	— US gpm (liter / s)
Turbo Compressor Outlet Pressure	— psi (kPa)
Turbo Compressor Outlet Temperature.....	— °F (°C)
Intake Air Flow	— cfm (liter / s)
Exhaust Gas Temperature.....	— °F (°C)
Exhaust Gas Flow	— cfm (liter / s)
Air-to-Fuel Ratio.....	— air : fuel
Radiated Heat to Ambient	— BTU / min (kW _m)
Heat Rejection to Coolant.....	— BTU / min (kW _m)
Heat Rejection to Exhaust	— BTU / min (kW _m)
Heat Rejection to Fuel *	— BTU / min (kW _m)
Heat Rejection to Aftercooler.....	— BTU / min (kW _m)

	STANDBY		PRIME POWER	
	60 hz	50 hz	60 hz	50 hz
	1800	1500	1800	1500
	675 - 775	675 - 775	675 - 775	675 - 775
	650 (485)	670 (500)	585 (436)	605 (585)
	314 (2165)	388 (2675)	282 (1944)	350 (2412)
	1995 (10.1)	1663 (8.4)	1995 (10.1)	1663 (8.4)
	70 (52)	50 (37)	70 (52)	50 (37)
	105 (6.6)	84 (5.3)	105 (6.6)	84 (5.3)
	87 (5.5)	68 (4.3)	87 (5.5)	68 (4.3)
	37 (255)	40 (272)	33 (228)	34 (234)
	415 (213)	440 (227)	380 (193)	395 (202)
	1380 (650)	1260 (595)	1290 (610)	1140 (540)
	840 (450)	970 (520)	795 (425)	915 (490)
	3200 (1510)	3240 (1530)	2905 (1370)	2860 (1350)
	27.5 : 1	23.9 : 1	28.9 : 1	24.9 : 1
	2000 (35)	2500 (44)	1800 (32)	2300 (40)
	8900 (156)	9400 (165)	7900 (139)	8100 (145)
	20000 (350)	20500 (360)	17000 (300)	17500 (308)
	450 (8)	450 (8)	450 (8)	450 (8)
	7400 (130)	7300 (128)	6200 (109)	5900 (104)

* Maximum heat rejection which occurs at rated speed, no load.

•• PRELIMINARY ••

- N.A. - Data is Not Available
- NA - Not Applicable to this Engine
- TBD - To Be Determined

ENGINE MODEL : QSX15-G8
DATA SHEET : DS-10302
DATE : 3Oct01
CURVE NO. : FR-10302